

CJV200 Series



High value in a small footprint, the Mimaki CJV200 Series of inkjet printers provides indoor and outdoor durable printing with an integrated cutter and easy-to-use software for the perfect stand-alone bundle. Available in 32-, 54- and 64-inch widths.

Specifications

NA Warranty	3-Years Coverage - 1 Year Warranty, 2 Years Parts Plus+
LATAM Warranty	2-Years Coverage
Heads	1
Head Type	On-demand piezo
Dropet Technology	Variable / Grayscale
Head Series	330
Head Arrangement	Single
Channels	8
Nozzles per Channel	400

For best results, always use Mimaki original inks.

Print Nozzles	1 head x 400 nozzles x 8 rows		
Print Resolution	1200 X 1200		
Minimum Dot Size	3pl		
Head Gap	Manual 0.5mm Adj.(1.5/2.0)		
Max Media Width	CJV200-75	CJV200-130	CJV200-160
	31.89 in (810.00 mm)	53.98 in (1371.00 mm)	63.78 in (1620.00 mm)
Max Media Thickness	0.04 in (1.00 mm)		
Max Media Dia	7.09 in (180.00 mm)		
Max Media Weight1	25kg or less		
Max Media Weight2	45kg or less w. OPT-J0502		
Media Cores	2 inch, 3 inch		
Max Printing Width	31.50 in (800.00 mm)		
Max Cutting Width	800		
Color LCD Control Panel	Yes		
Nozzle Check Unit (NCU)	Yes		
Integrated Media Cutting	Yes		
Media Heaters	3 - Pre, Print, Post		
ID-cut	Yes		
Tool Stations	1		
Supported Tools	Swivel / Eccentric Cutter		
Swivel Cutting Pressure	450g		
Cut Speed Max	300mm/sec		
Acceleration Max	0.5G		
Cutting Pressure	10-450gf		
Response Time	10 times/sec		
Repetition Accuracy	±0.2mm		
Maximum Pressure	450g		
Maximum speed	Yes		
RIP	RasterLink7		
Cut	FineCut9		

For best results, always use Mimaki original inks.

Design	Simple Create		
PICT	Yes		
Mimaki Remote Access (MRA)	Yes		
Connection Interface	Ethernet 1000BASE-T, USB 2.0 Hi-speed		
Dimensions	CJV200-75:	77.17 in (1960.00 mm) X 29.45 in (748.00 mm) X 53.94 in (1370.00 mm)	
	CJV200-130:	99.21 in (2520.00 mm) X 29.45 in (748.00 mm) X 53.94 in (1370.00 mm)	
	CJV200-160:	109.06 in (2770.00 mm) X 29.45 in (748.00 mm) X 53.94 in (1370.00 mm)	
Weight	CJV200-75	CJV200-130	CJV200-160
	231.53 lb (105.00 kg)	286.65 lb (130.00 kg)	308.70 lb (140.00 kg)
Required Power	AC(100~120V / 200~240V±10%)×2 50/60Hz±1Hz		
Power Consumption - Max	1,320W x2		
Power Consumption - Avg	1,000W or less		
Power Consumption - Sleep	4.5W or less		
Standby	Not more than 45 dB		
Continuous Operation	Not more than 59 dB		
Temperature	68-86F (20-30C)		
Guaranteed Accuracy	68-77F (20-25C)		
Humidity	35~65%RH(Non-condensing)		
Dust Level	Equivalent to general office		
Max Printing Speed	236.81 sqft (22.00 sqm)		
MPS Print Mode	4 Color 600x1200 4pass (160 Size)		
Machine Certifications	VCCI class A, FCC class A, ETL IEC 62368-1,CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, Energy Star, RCM, KC		
Ink Type/Color	Eco-Solvent SS21 CMYK Lc, Lm, Lk, Or, W SS22 CMYK Lc, Lm, Lk, Or, W		

Please visit us at: <https://www.mimakiusa.com>

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc.

Rev. 6/30/26

For best results, always use Mimaki original inks.