Specification Sheet

JFX200-2513 EX



The Mimaki JFX200-2513 EX large format UV-LED flatbed printer offers expanded capabilities with greater productivity and functionality. It can be used in industrial environments for component marking, membrane switch touchpads, dashboard panels, mass object customization, and more.

Specifications

NA Warranty	1 Year
LATAM Warranty	1 Year
Heads	3
Head Type	On-demand piezo
Droplet Technology	Variable / Grayscale
Head Arrangement	2 Staggered, 1 In-Line
Print Resolution	1200 X 1200
Minimum Dot Size	5pl

For best results, always use Mimaki original inks.

Head Gap	1.2 to 3mm

Max Media Width	**JFX200-1213 EX**	**JFX200-2513 EX**
	50.00 in (1270.00 mm)	98.43 in (2500.00 mm)

Max Media Length	1300
Max Media Thickness	1.97 in (50.00 mm)
Max Media Weight1	50kg / sqm
Max Printing Width	50.00 in (1270.00 mm)
Max Printing Length	1300
Nozzle Check Unit (NCU)	Yes
Vacuum Bed	Yes
Vacuum Zones	2
Media Registration	Threaded Pins
Gap Check Laser Sensor	Yes
Lamp Type	UV-LED
Curing Units	2
Cooling	Liquid
ID-cut	Yes
RIP	RasterLink7
PICT	Yes
Connection Interface	Ethernet 1000BASE-T, USB 2.0 Hi-speed

Dimensions		
	JFX200-1213 EX:	125.98 in (3200.00 mm) X 96.46 in (2450.00 mm) X 49.21 in (1250.00 mm)
	JFX200-2513 EX:	173.23 in (4400.00 mm) X 88.58 in (2250.00 mm) X 49.21 in (1250.00 mm)

Weight	**JFX200-1213 EX**	**JFX200-2513 EX**
	1124.55 lb (510.00 kg)	1433.25 lb (650.00 kg)

Required Power	200 to 240 V ±10 % AC, 50/60 Hz ±1 Hz, max. 12 A
Power Consumption - Max	2880W or Less
Standby	Not more than 55 dB

For best results, always use Mimaki original inks.

Continuous Operation	Not more than 75 dB
Temperature	68-86F (20-30C)
Guaranteed Acccuracy	68-77F (20-25C)
Humidity	35~65%RH(Non-condensing)
Dust Level	Equivalent to general office
Max Printing Speed	269.10 sqft/hr (25.00 sqm/hr)
MPS Print Mode	4 Color + White 300x300 4Pass
Machine Certifications	VCCI Class A, FCC Class A, UL62368-1 ETL compliance, CE marking (EMC Directive, Low Voltage Directive, Machinery Directive), IEC/EN62368-1 (CB certified), RoHS compliant, REACH compliant, RCM
Ink Type/Color	UV-LED | LH-100 CMYK Lc, Lm, W, Cl | LUS-120 CMYK W, Cl | LUS-150 CMYK Lc, Lm, W, Cl | LUS-211 CMYK W, Cl | LUS-350 CMYK W, Cl | PR-200 Primer
Media Cores	2500

Please visit us at: https://www.mimakiusa.com

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc. Rev. 10/1/26

For best results, always use Mimaki original inks.