

JV200 Series



The Mimaki JV200 Series of eco-solvent, roll-to-roll printers are affordable, entry-level models that can produce indoor and outdoor prints on a large selection of media including vehicle wraps, banners, wall murals and posters. They can be configured in 54 and 64-inch widths and offer either dual 4-color or 8-color ink sets.

Specifications

NA Warranty	3-Years Coverage - 1 Year Warranty, 2 Years Parts Plus+
LATAM Warranty	2-Years Coverage
Heads	1
Head Type	On-demand piezo
Dropet Technology	Variable / Grayscale
Head Series	330
Head Arrangement	Single
Channels	8

For best results, always use Mimaki original inks.

Nozzles per Channel	400
Print Nozzles	1 head x 400 nozzles x 8 rows
Print Resolution	1200 X 1200
Minimum Dot Size	3pl
Head Gap	Manual 0.5mm Adj.(1.5/2.0)
Max Media Width	JV200-130 53.98 in (1371.00 mm) JV200-160 63.78 in (1620.00 mm)
Max Media Thickness	0.04 in (1.00 mm)
Max Media Dia	7.09 in (180.00 mm)
Max Media Weight1	25kg or less
Max Media Weight2	45kg or less w. OPT-J0502
Media Cores	2 inch, 3 inch
Max Printing Width	53.58 in (1361.00 mm)
Color LCD Control Panel	Yes
Nozzle Check Unit (NCU)	Yes
Integrated Media Cutting	Yes
Media Heaters	3 - Pre, Print, Post
ID-cut	Yes
RIP	RasterLink7
Design	Simple Create
PICT	Yes
Mimaki Remote Access (MRA)	Yes
Connection Interface	Ethernet 1000BASE-T, USB 2.0 Hi-speed
Dimensions	JV200-130: 99.21 in (2520.00 mm) X 29.45 in (748.00 mm) X 53.94 in (1370.00 mm) JV200-160: 109.06 in (2770.00 mm) X 29.45 in (748.00 mm) X 53.94 in (1370.00 mm)
Weight	JV200-130 286.65 lb (130.00 kg) JV200-160 308.70 lb (140.00 kg)
Required Power	AC(100~120V / 200~240V±10%)×2 50/60Hz±1Hz
Power Consumption - Max	1,320W x2

For best results, always use Mimaki original inks.

Power Consumption - Avg	1,000W or less
Power Consumption - Sleep	4.5W or less
Standby	Not more than 45 dB
Continuous Operation	Not more than 59 dB
Temperature	68-86F (20-30C)
Guaranteed Accuracy	68-77F (20-25C)
Humidity	35~65%RH(Non-condensing)
Dust Level	Equivalent to general office
Max Printing Speed	236.81 sqft (22.00 sqm)
MPS Print Mode	4 Color 600x1200 4pass (160 Size)
Machine Certifications	VCCI class A, FCC class A, ETL IEC 62368-1, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, Energy Star, RCM, KC
Ink Type/Color	Eco-Solvent SS21 CMYK Lc, Lm, Lk, Or, W SS22 CMYK Lc, Lm, Lk, Or, W

Please visit us at: <https://www.mimakiusa.com>

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc.

Rev. 8/17/26

For best results, always use Mimaki original inks.