

TS330 Series



The Mimaki TS330 Series of production textile inkjet printers offers the latest technologies for producing superior image quality on a wide range of fabrics. The 64-inch wide TS330-1600 sublimation transfer printer offers high-speed production, while the 128-inch wide TS330-3200DS printer is the best of both worlds, doubling as a sublimation unit for printing to transfer paper and as a direct-to-textile unit for printing on polyester fabrics

Specifications

NA Warranty	1 Year
LATAM Warranty	1 Year
Heads	2
Head Type	On-demand piezo
Dropet Technology	Variable / Grayscale
Head Series	330 Series
Head Arrangement	Staggered

For best results, always use Mimaki original inks.

Channels	8	
Nozzles per Channel	400	
Print Nozzles	2 heads x 400 nozzles x 8 rows	
Print Resolution	1200 X 600	
Minimum Dot Size	4pl	
Head Gap	Manual 0.5mm Adj.(3.0/3.5/4.0mm)	
Max Media Width	TS330-1600	TS330-3200DS
	63.78 in (1620.00 mm)	127.95 in (3250.00 mm)
Max Media Thickness	0.04 in (1.00 mm)	
Max Media Dia	9.84 in (250.00 mm)	
Max Media Weight1	45 or less	
Media Cores	2 inch, 3 inch	
Max Printing Width	63.39 in (1610.00 mm)	
Color LCD Control Panel	Yes	
Nozzle Check Unit (NCU)	Yes	
Integrated Media Cutting	Yes	
Media Heaters	1 - Post	
ID-cut	Yes	
RIP	RasterLink7 & TxLink4	
PICT	Yes	
Mimaki Remote Access (MRA)	Yes	
Connection Interface	Ethernet 1000BASE-T, USB 2.0 Hi-speed	
Dimensions	TS330-1600: 124.80 in (3170.00 mm) X 32.28 in (820.00 mm) X 51.38 in (1305.00 mm)	
Weight	TS330-1600	
	529.20 lb (240.00 kg)	
Required Power	Single phase AC100~120V/200~240V±10%50/60Hz±1HZ x1	
Power Consumption - Max	1440W or less	

For best results, always use Mimaki original inks.

Power Consumption - Avg	1440W or less
Standby	Not more than 58 dB
Continuous Operation	Not more than 65 dB
Temperature	68-86F (20-30C)
Guaranteed Accuracy	68-77F (20-25C)
Humidity	35~65%RH(Non-condensing)
Dust Level	Equivalent to general office
Max Printing Speed	1453.13 sqft (135.00 sqm)
MPS Print Mode	4 Color 300x600 1Pass
Machine Certifications	ETL IEC 62368-1, CB, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), REACH, VCCI Class A, FCC Class A, EAC, KC, RCM, UKCA, EnergyStar
Ink Type/Color	Transfer Sublimation Sb411 BIMYK Sb410 BIMYK, Lb, Lm, Lk, Fp, Fy
Ink Tanks	Option - 10Kg
Promo Price	29929.0

Please visit us at: <https://www.mimakiusa.com>

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc.

Rev. 6/30/26

For best results, always use Mimaki original inks.