

Tx330 Series



The Mimaki Tx330-1800 digital textile printer is a hybrid model that can print both direct-to-fabric and to paper. It utilizes a near-waterless system that eliminates steps and equipment for many natural fabrics, and requires no coating, steaming, or washing. This 75-inch wide model is capable of running two inks sets to provide maximum versatility.

Specifications

NA Warranty	1 Year
LATAM Warranty	1 Year
Heads	2
Head Type	On-demand piezo
Dropet Technology	Variable / Grayscale
Head Series	330 Series
Head Arrangement	Staggered
Channels	8
Nozzles per Channel	400

For best results, always use Mimaki original inks.

Print Nozzles	2 heads x 400 nozzles x 8 rows	
Print Resolution	1800 X 1200	
Minimum Dot Size	3.5pl	
Head Gap	Manual 1mm Adj.(3.0/4.0/5.0/6.0/7.0mm)	
Max Media Width	Tx330-1800 76.77 in (1950.00 mm)	Tx330-1800B 74.80 in (1900.00 mm)
Max Media Thickness	0.20 in (5.00 mm)	
Max Media Dia	9.84 in (250.00 mm)	
Max Media Weight¹	40 or less	
Media Cores	2 inch, 3 inch	
Max Printing Width	76.38 in (1940.00 mm)	
Color LCD Control Panel	Yes	
Nozzle Check Unit (NCU)	Yes	
ID-cut	Yes	
RIP	RasterLink7 & TxLink5	
PICT	Yes	
Mimaki Remote Access (MRA)	Yes	
Connection Interface	Ethernet 1000BASE-T, USB 2.0 Hi-speed	
Dimensions	Tx330-1800: 127.17 in (3230.00 mm) X 37.99 in (965.00 mm) X 73.11 in (1857.00 mm)	
	Tx330-1800B: 127.17 in (3230.00 mm) X 75.28 in (1912.00 mm) X 74.80 in (1900.00 mm)	
Weight	Tx330-1800 641.66 lb (291.00 kg)	Tx330-1800B 1371.51 lb (622.00 kg)
Required Power	Single-phase AC200-240V±10%/5A? 50/60±1Hz x1	
Power Consumption - Max	300W or less	
Power Consumption - Avg	170W or less	
Power Consumption - Sleep	4.5W or less	

For best results, always use Mimaki original inks.

Standby	Not more than 54 dB
Continuous Operation	Not more than 59 dB
Temperature	68-86F (20-30C)
Guaranteed Accuracy	68-77F (20-25C)
Humidity	35~65%RH(Non-condensing)
Dust Level	Equivalent to general office
Max Printing Speed	645.83 sqft (60.00 sqm)
MPS Print Mode	4 Color 600x600 3Pass Sb420
Machine Certifications	VCCI Class A, FCC Class A, IEC 62368-1 ETL compliance, CE marking (EMC Directive, Low Voltage Directive, Machinery Directive, RoHS Directive), CB certified, REACH, EnergyStar, RCM marking, KC certified, UKCA marking
Ink Type/Color	Transfer Sublimation / Direct Sublimation TP410 CMYK Bl,R,G,Lk Sb411 BIMYK Sb420 BIMYK Lm, Lb
Max Media Weight	40 or less

Please visit us at: <https://www.mimakiusa.com>

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc.

Rev. 7/1/26

For best results, always use Mimaki original inks.