Specification Sheet

TxF150 Series

The Mimaki TxF150-75 entry-level direct-to-film (DTF) inkjet printer is packed with Mimaki technology to overcome the common ink ejection and ink sedimentation issues of current DTF printers in the market. This 32-inch wide model enables the creation of intricate designs on an expansive range of fabrics, from cotton, mixed textiles, polyester, and even darker shades.

Specifications

NA Warranty	1 Year
LATAM Warranty	1 Year
Heads	1
Head Type	On-demand piezo
Dropet Technology	Variable / Grayscale
Head Series	Mimaki
Head Arrangement	Single

For best results, always use Mimaki original inks.

Channels	8
Nozzles per Channel	180
Print Nozzles	1 head x 180 nozzles x 8 rows
Print Resolution	1440 X 1440
Minimum Dot Size	7pl
Head Gap	Manual 0.5mm Adj.(2.0/2.5/3.0mm)

Max Media Width	**TxF150-75**
	31.89 in (810.00 mm)

Max Media Thickness	0.04 in (1.00 mm)
Max Media Dia	9.84 in (250.00 mm)
Max Media Weight1	45 or less
Media Cores	2 inch, 3 inch
Max Printing Width	31.50 in (800.00 mm)
Color LCD Control Panel	Yes
Nozzle Check Unit (NCU)	Yes
Integrated Media Cutting	Yes
Media Heaters	3 - Pre, Print, Post
ID-cut	Yes
RIP	RasterLink7
PICT	Yes
Mimaki Remote Access (MRA)	Yes
Connection Interface	Ethernet 1000BASE-T, USB 2.0 Hi-speed
Dimensions	**TxF150-75:** 77.36 in (1965.00 mm) X 27.56 in (700.00 mm) X 54.80 in (1392.00 mm)

Weight	**TxF150-75**
	396.90 lb (180.00 kg)

Required Power	Single phase AC100~120V/200~240V±10%, 50/60Hz±1Hz
Power Consumption - Max	900W or less

For best results, always use Mimaki original inks.

Power Consumption - Avg	170W or less
Power Consumption - Sleep	4.9W or less
Standby	Not more than 45 dB
Continuous Operation	Not more than 65 dB
Temperature	68-86F (20-30C)
Guaranteed Acccuracy	68-77F (20-25C)
Humidity	35~65%RH(Non-condensing)
Dust Level	Equivalent to general office
Max Printing Speed	35.52 sqft (3.30 sqm)
MPS Print Mode	4C + White 720x720 8Pass
Machine Certifications	VCCI Class A / FCC Class A / IEC 62368-1 compliant ETL / CE marking (EMC Directive, Low Voltage Directive, Machinery Directive) / CB Certification / ROHS / REACH / Energy Star / RCM (Australia) / KC (Korea)
Ink Type/Color	Direct-To-Film (DTF) | PHT50 CMYK W

Please visit us at: https://www.mimakiusa.com

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc. Rev. 10/1/26

For best results, always use Mimaki original inks.