Specification Sheet

UCJV300-75

Specifications

NA Warranty	1 Year
LATAM Warranty	1 Year
Heads	2
Head Type	On-demand piezo
Droplet Technology	Variable / Grayscale
Head Arrangement	Inline
Channels	8
Nozzles per Channel	320
Print Nozzles	2 heads x 320 nozzles x 4 rows
Print Resolution	1200 X 1200
Minimum Dot Size	7pl
Head Gap	Manual 0.5mm Adj.(2.0/2.5/3.0)
Max Media Width	**UCJV300-75**: 31.89 in (810.00 mm) / **UCJV300-160**: 63.78 in (1620.00 mm)
Max Media Thickness	0.04 in (1.00 mm)
Max Media Dia	9.84 in (250.00 mm)
Max Media Weight1	40kg or less
Media Cores	2 inch, 3 inch
Max Printing Width	31.50 in (800.00 mm)
Max Cutting Width	800
Color LCD Control Panel	Yes
Nozzle Check Unit (NCU)	Yes

For best results, always use Mimaki original inks.

Integrated Media Cutting	Yes
Lamp Type	UV-LED
Curing Units	2
Cooling	Air
ID-cut	Yes
Tool Stations	1
Supported Tools	Swivel / Eccentric Cutter, Pen
Cut Speed Max	300mm/sec
Acceleration Max	0.5G
Cutting Pressure	10-450 gf
Response Time	10 times/sec
Buffer Memory	32 Mb
Repetition Accuracy	±0.2 mm
RIP	RasterLink7
Cut	FineCut9
Other	Artista UV Texture Library
Connection Interface	Ethernet 1000BASE-T, USB 2.0 Hi-speed
Dimensions	**UCJV300-75:** 82.28 in (2090.00 mm) X 30.55 in (776.00 mm) X 58.07 in (1475.00 mm) **UCJV300-160:** 114.17 in (2900.00 mm) X 30.55 in (776.00 mm) X 58.07 in (1475.00 mm)

Weight	**UCJV300-75**	**UCJV300-160**
	317.52 lb (144.00 kg)	414.54 lb (188.00 kg)

Required Power	Single phase (AC100-120 / 200-240V±10%, 50/60Hz±1Hz)
Power Consumption - Max	1,920 W
Power Consumption - Avg	1,440 W
Standby	55 dB or less
Continuous Operation	65 dB or less
Temperature	68-86F (20-30C)

For best results, always use Mimaki original inks.

Guaranteed Acccuracy	68-77F (20-25C)
Humidity	35~65%RH(Non-condensing)
Dust Level	Equivalent to general office
Max Printing Speed	193.75 sqft/hr (18.00 sqm/hr)
MPS Print Mode	4 Color 300x600 4Pass
Machine Certifications	VCCI Class A, FCC Class A, IEC 62368-1 ETL compliance, CE marking (EMC Directive, Low Voltage Directive, Machinery Directive), CB certified, RoHS, REACH, EnergyStar, RCM marking
Ink Type/Color	UV-LED | LUS-170 CMYK Lc, Lm, W, Cl | LUS-200 CMYK W
Swivel Cutting Pressure	450g
Maximum Pressure	450g
Maximum speed	Yes

Please visit us at: https://www.mimakiusa.com

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

All specifications are subject to change; consult your authorized Mimaki representative for current information.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc. Rev. 9/28/26

For best results, always use Mimaki original inks.