STANDARD PLUG-IN SOFTWARE FOR ADOBE® ILLUSTRATOR® CC

The combination of FineCut8 and a register mark reading sensor allows calibrated inclination of coordinates or distance to assure accurate cutting. To prevent incorrect cutting, long contour cutting lines are split and individually cut. This split cut function avoids having the blade cut the media/substrate beyond the [Main features] Simple and direct cutting from Adobe Illustrator / "Multiple cut function" allows the plotter to cut on the same contour cutting line several times with different cut conditions. "Split cut function" prevents an overcut of the media/substrate.











CFL-605RT SPECIFICATIONS | ACCESSORIES

Туре		Flatbed cutting plotter		Product name		QTY per package	
Driving method		X/Y/Z/@ 4 axes: DC servo motor	number	Product name	Cc	ompatible product model	
Material holding method		Air suctioning by a vacuum unit	SPA-0183	Pen holder for MITSUBISHI	1	CG/CF series	
Maximum media		630mm×530mm	SPA-0183				Co
Cutting area		610mm×510mm	SPC-0726	Refill for MITSUBISHI	10	CG/CE series	Cor
Maximur	n cutting speed	XY: 423 mm/s (45° angle direction) Z: 30 mm/s	SPC-0726	ballpoint pen	10	CG/CF series	Co
Maximum downforce pressure		Eccentric cutter:1,000g / Tangential cutter and Creasing roller: 1,500 g	SPB-0086	Super hard edge 2°x 10 mm	5	CFL	
Maximum media thickness		Reciprocating cutter: 10 mm / Tangential cutter: 2 mm	3FB-0080				
Maximum media weight		20 kg (This is not one-point-load strength)	SPA-0260	Cutter holder 07L	1	CFL	
Static accuracy	Repeatability	0.2 mm or lower (Material shrinkage is ignored)	SPB-0043	High-speed steel blade 30°	200	CF series	
	Distance accuracy	Moving distance × ±0.2% or lower or ±0.1 mm or lower Larger value is applied	SPB-0045	Carbide blade 30°	3	CF series	
	Original repetition accuracy	0.1 mm or lower	SPA-0261	Tangential	1	CFL	
A unit		Attachable tools: Eccentric cutter, Pen	3FA-0201	Cutter holder 2N a		CFL	
B unit		Attachable tools: Reciprocating/Tangential cutter, Creasing roller	SPA-0259	Eccentric cutter holder C	1	CFL	
Comman	d	MGL-II c3					
Interface		USB 2.0(High Speed), RS-232C, Ethernet	SPB-00B5	Eccentric cutter blade C	3	All cutting plotter models	
Power sp	ecification	Single phase AC 100-120 V/200-240 V, 50/60 Hz					S
Noise level		70 db or lower(The maximum level is generated while a reciprocating cutter or a vacuum blower is used.)	SPC-0785	Felt mat 605	1	CFL	
Power consumption		500W	SPC-0786	Cutting mat 605	1	CFL	
Dimensions (W×D×H)		1,320mm×1,045mm×1,100mm	SPC-0787	Adsorption sheet	1	CFL	
Weight		109 kg or lower (Blower, 20 kg, included)	SPA-0262	Creasing holder L	1	CFL	
Warranty period		1 year	SPB-0087	Creasing roller φ9	1	CFL	
Certifications		VCCI class A, CE marking (Machinery directive, RoHS directive), CB, UL 60950-1, REACH, FCC class A	SPB-0030	Swivel Blade for PVC with low-pressure	3	All cutting plotter models	
		"	SPB-0006	Swivel Blade for reflecting sheet	2	All cutting plotter models	
			SPB-0007	Swivel Blade for fluorescent sheet	3	All cutting plotter models	
			SPB-0001	Swivel Blade for PVC sheet	3	All cutting plotter models	
			SPB-0003	Swivel Blade for small letters	3	All cutting plotter models	
			SPA-0001	Cutter holder	1	All cutting plotter models	

	number	Troduct name		mpatible product model	14012	
	SPA-0183	Pen holder for MITSUBISHI	1	CG/CF series	One refill is attached Compatible refill: SPC-0726	
1	SPC-0726	Refill for MITSUBISHI ballpoint pen	10	CG/CF series	Compatible holder: SPA-0183	
ı	SPB-0086	Super hard edge 2°x 10 mm	5	CFL	One blade is attached as a standard accessory	
	SPA-0260	Cutter holder 07L	1	CFL	Standard accessory	
	SPB-0043	High-speed steel blade 30°	200	CF series	Standard accessory	
	SPB-0045	Carbide blade 30°	3	CF series		
ı	SPA-0261	Tangential Cutter holder 2N a	1	CFL	Standard accessory	
	SPA-0259	Eccentric cutter holder C	1.	CFL	Standard accessory	
	SPB-0085	Eccentric cutter blade C	3	All cutting plotter models	One blade is attached as a standard accessory Compatible holder: SPA-0001/SPA-0090/SPA-0259	
	SPC-0785	Felt mat 605	1	CFL	Standard accessory	
	SPC-0786	Cutting mat 605	1	CFL	Standard accessory	
	SPC-0787	Adsorption sheet	1	CFL	100 m per roll	
	SPA-0262	Creasing holder L	1	CFL	Standard accessory	
	SPB-0087	Creasing roller φ9	1	CFL	Standard accessory	
	SPB-0030	Swivel Blade for PVC with low-pressure	3	All cutting plotter models		
	SPB-0006	Swivel Blade for reflecting sheet	2	All cutting plotter models		
	SPB-0007	Swivel Blade for fluorescent sheet	3	All cutting plotter models		
	SPB-0001	Swivel Blade for PVC sheet	3	All cutting plotter models		
	SPB-0003	Swivel Blade for small letters	3	All cutting plotter models		
	SPA-0001	Cutter holder	1	All cutting plotter models	y	
	SPA-0090	Cutter holder	1	All cutting plotter models	Standard accessory	
	OPT-S1005	Blade tip adjuster	1	All cutting plotter models	Loupe	
	OPT-C0066	Blade tip adjuster	1	All cutting plotter models	Dial type	
	SPA-0163	Grease	1	All cutting plotter models	Standard accessory	

Some of the samples in this brochure are artificial renderings. Specifications, design and dimensions stated may be subject to change without notice (for technical improvements, etc.)



Mimaki USA, Inc. | 150-A Satellite Blvd. Suwanee, GA 30024 | 888-530-4021 | info@mimakiusa.com © 2015 Mimaki USA, Inc. All rights reserved. Ver. 1.1

CFL-605RT



Mimaki CFL-605RT Compact Flatbed Cutting Plotter

