

RIMSLOW SERIES

FOR TEXTILE PRE-TREATMENT AND POST-TREATMENT

A COMPLETE LINE OF TEXTILE PRE-TREATMENT AND POST-TREATMENT MACHINES







CHOOSE THE SET THAT BENEFITS YOU THE MOST





DIRECT SUBLIMATION /
TEXTILE PIGMENT
STARTING SET DIRECT-TO-TEXTILE PRODUCTION SET









Steaming TR300-1850S Starting set with either direct sublimation (4C) or textile pigment inks (7C). Or our unique hybrid function with both inks (2x 4C) in one printer!

INK AND CORRESPONDING PRE-TREATMENT MACHINE FOR CONSISTENT RESULTS

We develop our pre-treatment machines for you to get the best out of our inks. Colour matching is facilitated in order to achieve steady colour results, even when they come from different production points or printing and post-processing facilities.

COLOURING TEST BEFORE THE PRODUCTION RUN

With the introduction of the new textile production line of pre-treatment, printing, and post-treatment machines, Mimaki can also conduct colouring tests adapted to your requirements. The colouring test makes sure you can start your production smoothly, as soon as the production line is set, without testing delay.

ONE-STOP SOURCE FOR YOUR TEXTILE PRODUCTION

By choosing your textile production line from Mimaki, you will need only one contact to assist you with any point of the production line, making sure it is in consistence with the preceding or following step. From the printer to the coating and washing machines, everything is covered by one support service, for your peace of mind. With vast global network of long-established partners and unparalleled textile printing heritage, Mimaki is here to support your business from start to finish.

PRODUCT LINE-UP

ТҮРЕ	Coating	Steaming		Washing / Coating
PRODUCT	TR300-1850C	TR300-1850S	TR600-1850C	TR600-1850W
MEDIA WIDTH	1,850mm			
PRODUCTION SPEED	100Lm/h	Acid dye ink (102°C/30min) 11 Lm/h	Acid dye ink (102°C/30min) 52 Lm/h	230Lm/h
		Reactive dye ink (102°C/15min) 22 Lm/h	Reactive dye ink (102°C/15min) 104 Lm/h	
		Disperse dye ink (180°C/8min) 41 Lm/h	Disperse dye ink (180°C/8min) 195 Lm/h	
		Pigment ink (160°C/6min) 55 Lm/h	Pigment ink (160°C/6min) 260 Lm/h	
TEMPERATURE	160°C	180°C		160°C
WATER TANK	50L	25L	50L	75L (Pre-treatment)
				340L x 2 (Washing)
HEATER TYPE	Electric			
DIMENSION (WxDxH)	2.6 x 1.7 x 1.1m	2.5 x 1.6 x 1.3m		2.7 x 4.8 x 2.4m

Specifications, design and dimensions stated in this folder may be subject to change without notice (for technical improvements, etc.) •
The corporate and merchandise names written on this folder are the trademark of the respective corporations • higher printers print using extreme fine dots, so colours may vary after replacement of the printing heads, also note that if using multiple printer unites, colours could vary slightly from one unit to other unit due to slight individual differences • Compositor's errors reserved.

www.mimakieurope.com