

# JFX600-2513



## Blazing Speed, High Definition

The Mimaki JFX600-2513 UV-LED flatbed printer is the fastest model in the world's best-selling JFX Series line. Productivity has never looked better. This state-of-the-art printer is geared for high accuracy, high image quality, and blazing speed.

- 16 print heads
- Print speeds up to 2,152 square feet per hour
- Equivalent to 67 boards per hour
- On machine job and maintenance control via Mimaki Print Controller (MPC)
- Industry leading Mimaki Core Technologies
- Print area of 98.425" x 51.181"; up to 2.362" thick
- Production workflow ready with MDL support
- Eco-friendly with low VOC, GREENGUARD Gold certified UV-LED inks
- Compact design

For best results, always use Mimaki original inks.

# Mimaki® JFX600-2513

<b>Printhead</b>	Sixteen on-demand piezo heads in a staggered array
<b>Print Resolutions</b>	600 x 600dpi, 600 x 1,200dpi, 1,200 x 1,200dpi
<b>Print Speed (4 Color Mode)</b>	up to 2,152.78 SqFt/Hr (200.0 m2/h)
<b>Maximum Print Area</b>	98.43" x 51.18" (2,500 x 1,300 mm)
<b>Maximum Media Width</b>	98.43" (2500 mm)
<b>Maximum Media Thickness</b>	up to 2.36" (60 mm)
<b>Maximum Media Weight</b>	110.2 lbs. (50kg/m <sup>2</sup> )
<b>Ink Type</b>	U.S. & Canada- LH-100, LUS-120, LUS-150 Mexico, Central & South America- LH-100, LUS-120, LUS-150
<b>Interface</b>	Ethernet 10,000 BASE-T
<b>Power Supply</b>	AC 200 – 240 V, 50/60 Hz
<b>Power Consumption</b>	x3 AC200-240±10% ~16kVA 50/60Hz±1Hz
<b>Operational Environment</b>	Temperature 68° – 86° F (15-30° C) Humidity: 35–65 % RH (Non condensing)
<b>Dimensions (W x D x H)</b>	207.48" x 110.24" x 62.99" (5,300x2,850x1,700mm)
<b>Weight</b>	2, 645.5 lbs. (1,200 kg)
<b>Certifications</b>	UL 775 ETL, CE Marking (EMC Directive, Low Voltage Directive, Machinery Directive), RoHS / REACH / EAC

UV-LED FLATBED PRINTER

98.43" X 51.18"

Please visit us at: [www.mimakiusa.com](http://www.mimakiusa.com)

Mimaki USA, Inc.  
150-A Satellite Blvd NE, Suwanee, GA 30024

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2020, Mimaki USA, Inc.

Rev. 04/20/22