

# UJV200 Series



ROLL-TO-ROLL UV-LED INKJET PRINTER

64"

54"

## High-Quality Printing Made Easier

UV-LED roll-to-roll printer with high image quality, simple operation, and stable output.

- High-quality printing
- Auto media feed alignment and adjustment
- Adjustable ink level adjustment
- Faster cleaning cycles
- New ELS-170 ink (meets or exceeds the EU- REACH regulations)
- Sharper fine lines and solid colors
- New Lami-Fit technology
- Print up to 3 layers without pull-back
- Reliable quality and performance even at speed
- Low odor, fast curing and eco-friendly

*For best results, always use Mimaki original inks.*

# Mimaki® UJV200 Series

<b>Printhead</b>	Single on-demand piezo head
<b>Print resolution</b>	Y: 600 dpi, 900 dpi, 1200 dpi X: 600 dpi, 1200 dpi
<b>Print speed (4 color mode)</b>	UJV200-160: Draft: 269.1 sqft/hr (25.0 sqm/hr); Standard: 150.7 sqft/hr (14.0 sqm/hr) UJV200-130: Draft: 236.8 sqft/hr (22.0 sqm/hr); Standard: 139.9 sqft/hr (13.0 sqm/hr)
<b>Maximum print width</b>	UJV200-160: 63.4 in (1610 mm) UJV200-130: 53.5 in (1360 mm)
<b>Media Thickness</b>	Up to 2 mm
<b>Media Weight</b>	Max 55 lbs (25 kg) roll weight
<b>Ink Type/Color</b>	ELS-170 ink sets CMYK, CMYK CMYK, CI, CI, W, W CMYK, W, W (*ELS-175/ *LUS-210 *LATAM Market Only)
<b>Ink Package Size</b>	1 L Bottle
<b>Interface</b>	(Recommended) Ethernet 1000BASE-T USB 2.0 Hi-Speed
<b>Power Supply</b>	AC100-120V (11A) or AC200-240V (5.5A)
<b>Power Consumption</b>	Max 1320W Standard 550W Min 4.5W
<b>Operational Environment</b>	Temperature: 68 - 86 °F (20-30 °C) Humidity: 35 - 65% Recommended temperature: 68 - 77 °F (20-25 °C) Dust level: General office level
<b>Dimensions (W x D x H)</b>	UJV200-160: 109.1 in x 29.4 in x 55.3 in (2770 mm x 748 mm x 1405 mm) UJV200-130: 99.2 in x 29.4 in x 55.3 in (2520 mm x 748 mm x 1405 mm)
<b>Weight</b>	UJV200-160: 352 lb (160 kg); UJV200-130: 342 lb (155 kg)
<b>Options</b>	<ul style="list-style-type: none"> <li>• OPT-J0422 - NCU</li> <li>• OPT-J0502 - Leveling Foot - Supports media weights up to 45 kg</li> <li>• OPT-J0545 - Ionizer 1600</li> <li>• OPT-01038 - UJV200 Ionizer OPT Connection Kit</li> </ul>
<b>Certifications</b>	IEC 62368 1, CE (EMC, Low Voltage, Machinery Directive, RoHS), REACH, VCCI Class A, FCC Class A, RCM, EAC, ENERGY STAR

ROLL-TO-ROLL UV-LED INKJET PRINTER

64"

54"

Please visit us at: [www.mimakiusa.com](http://www.mimakiusa.com)

Mimaki USA, Inc.  
4851 Thurmon Tanner Parkway, Suite 100, Flowery Branch, GA 30542

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2026, Mimaki USA, Inc.

Rev. 03/31/26